

Brand		NEOlift
Model		NPML10
Power type		Electric
Operation type		Seated
Steering type		Electric
Load capacity	kg	1000
Front overhang/rear overhang	mm	268/220
Wheelbase	mm	862
Service weight	kg	2400
Tire type		Solid rubber
Drive wheel/carrying wheel		15*4.5-8front/300-12rear
Overall length/overall width/overall height	mm	1350/1020/2050
Load center	mm	500
Max lifting height	mm	3000
Mast extended height (with shelves)	mm	3690
Mast closed height	mm	2050
For carrier height	mm	900
Mast, front/rear tilt		6~12 <sup>0</sup>
Outer turning radius	mm	1450
Fork adjustment range	mm	240~900
Minimum right angle channel width	mm	1960
Forks, length/thickness	mm	1070/35
Minimum ground clearance	mm	100
Maximum driving speed	km/h	13
Lifting speed, without load/with load	mm/s	265/220
Maximum lowering speed	mm/s	380
Climbing ability(with load/without load)	%	10/15
Walking control type		Continuously variable speed
Traveling motor power (AC)	kw	4
Drive motor control		Intelligent
Battery type		Lithium
Battery capacity	АН	140
Battery voltage	V	80
Battery weight	kg	200
Battery box dimensions (length, width, height)	mm	900x350x300
Fully charged running time	Н	6-7
		1